



COMMERCIAL DRYER (FRONT CONTROL) FOR VENDED LAUNDRY APPLICATIONS

CD10EC - CD10GC

10 KG

FEATURES

- **Superior airflow**
 - Advanced blower system produces airflow of 220 cu. Ft. per minute
 - Fast-drying results with advanced airflow pattern
 - Minimum dry time
- **Large capacity**
Large 7.0 cu. ft. cylinder
- **Door opening of 2.06 sq. ft. for fast and easy loading and unloading**
- **Time savings**
Large, easy-clean lint filter is located upfront

CONTROL

- **Micro-Display Control (MDC)**
Offering the most essential features and programming options, the Micro-Display Control (MDC) on IPSO commercial dryers is user-friendly and features an attractive, easy-to-read design
- **Coin countdown start**
Displays vend price and countdown coin and cycle time
- **Touch pad control**
Offers touch pad selection and combines both temperature and cycle
- **Sound and light indicators**
Indicate cycle status and coin validation
- **Activation options**
Available with coin drop installed, card ready or coin ready models
- **Manual programming and audit**
Program and audit use via the control panel



| | CD10EC | CD10GC |
|-----------------------------------|-------------------|------------------------------------|
| MODEL NUMBER | BDEBXAGS433AW01 | BDGBXAGS303AW01 BDGBXAGW303AW01 |
| CONTROL | MDC | MDC |
| CONTROL LOCATION | 10° front | 10° front |
| DRUM | | |
| CAPACITY (KG) | 10 | 10 |
| CYLINDER VOLUME (L) | 198 | 198 |
| MOTOR | | |
| POWER (kW) | 0,25 | 0,25 |
| CABINET | | |
| CYLINDER FINISH | galvanized | galvanized |
| COLOUR | white | white |
| DOOR TYPE | solid | solid / window (BDGBXAGW303AW01) |
| HEATING | | |
| HEAT SOURCE | electric | gas |
| HEATING POWER | 4 000 kW | 25 000 BTU |
| CONNECTION | | |
| GAS INLET CONNECTION (MM) | N/A | 9,5 |
| EXHAUST OUTLET DIAMETER (MM) | 102 | 102 |
| EXHAUST AIRFLOW (LITERS/SEC) | 105 | 105 |
| OPERATION | | |
| CYCLES | 4 | 4 |
| CYCLE INDICATOR LIGHTS | yes | yes |
| POWER | | |
| ELECTRICAL REQUIREMENTS | 240V / 50Hz / 1Ph | 240V / 50Hz / 1Ph |
| TRANSPORT DATA | | |
| GROSS WEIGHT (KG) | 73 | 73 |
| NET WEIGHT (KG) | 68 | 68 |
| DIMENSIONS H X W X D (MM) | 1126 x 683 x 711 | 1092 x 683 x 711 |
| PACKING DIMENSIONS H X W X D (MM) | 1156 x 762 x 864 | 1156 x 762 x 864 |
| VOLUME (m³) | 0,76 | 0,76 |

* heights may slightly vary, depending on the leveling adjustments

| (mm) | A* | B* | C* | D | E | F | G | H | I | J | K | L | M |
|------------------|------|-----|-----|-----|-----|-----|------|-----|------|-----|-----|-----|-----|
| CD10C - electric | 1126 | 938 | 392 | 102 | 391 | 683 | 114* | 10 | 203 | 711 | 597 | - | - |
| CD10C- gas | 1126 | 938 | 392 | 102 | 70 | 60 | 391 | 683 | 114* | 10 | 203 | 711 | 597 |

* with leveling legs turned into base
Exhaust openings are 102 mm metal ducting

electric

gas