

IA180 | IA240 | IA280

Hardmount

Washer-Extractor

Veeco

LAUNDRY SYSTEMS

T: 1300 853 644 W: www.veeco.com.au

VEECO Laundry Systems
1 Granite Place
Welshpool 6106, WA
Phone: 1300 853 644
www.veeco.com.au
IPSO-Partner for Western Australia
& Northern Territory



FEATURES

- Rigid mounted, normal spin, up to 100G factor
- Stainless steel drum and tub
- Patented soap hopper
- Easy access to all vital parts from the front
- Large door opening for easy loading & unloading
- High capacity water inlets (IA280)
- Large drain valve (Ø 76 mm)

OPTIONS

- Coin operated
- Stainless steel front and side panels
- Liquid soap connection and pumps
- Steam heating version
- ECO version: Lower kW rating on request
- 3rd water inlet
- High capacity water inlets (IA180, IA240)

CONTROLS OPTIONS

- Aries / Aries Elite – fully programmable control with 20 Pre-set programs and memory up to 99.
- Aries Micro – Programmable control with 6 programs (+2 cycle modifiers and Imbalance detection)



SMART DRUM TECHNOLOGY

Extra mechanical action thanks to its cascading shape of the surface



EXTRA LARGE DOOR OPENING

For easy loading and unloading



HIGH CAPACITY WATER INLETS

For shorter wash cycles




SmartWAVE automatically determines the absorption ability of the load at the start of the cycle, resulting in optimized water levels throughout the cycle.

		IA180	IA240	IA280
INNERDRUM				
Capacity 1:09	kg (lb)	20(44)	27(60)	31(68)
Capacity 1:10	kg (lb)	18(40)	24(53)	28(62)
Volume	litres	180	240	280
Diameter	mm	750	750	750
DRUM SPEED				
Wash	rpm	42	42	42
Extraction	rpm	490 (690)*	490 (690)*	490 (690)*
G-FACTOR		100 standard 200*	100 standard 200*	100 standard 200*
HEATING				
Electricity	kW	12 - 18	18	21,9
Steam	bar	1-8	1-8	1-8
Hot water	°C	90	90	90
Sound pressure level	dB (A)	< 65	< 65	< 65
Water valves connection	BSP	3/4"	3/4"	3/4"
Water pressure	kPa	100-800	100-800	100-800
Rec. water pressure	kPa	300-500	300-500	300-500
Water inlet	l/min	20	20	20
Drain valve	outer Ø mm	76	76	76
Flow amount with drain valve	l/min	210	210	210
Steam valve connection	BSP	1/2"	1/2"	1/2"
Steam pressure	kPa	100-800	100-800	100-800
DIMENSIONS				
Size H*W*D	mm	1410×890×915	1410×890×1060	1410×890×1135
Net weight	kg	255 (315)*	275 (330)*	290 (355)*
TRANSPORT DATA				
Packed H*W*D	mm	1550×925×970	1550×925×1130	1550×925×1190
Gross weight	kg	270 (335)*	290 (355)*	305 (385)*

* 200 G-factor execution

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	P	Q	R	S
IA180	890	915	1410	815	465	280	130	1212	1297	113	218	303	625	1270	1317	528	54	120
IA240	890	1060	1410	960	465	280	130	1212	1297	113	218	303	625	1270	1317	528	54	120
IA280	890	1135	1410	1035	465	280	130	1212	1297	113	218	303	625	1270	1317	528	54	120
	W	D	H															



- | | | |
|--------------------------|---------------------------|------------------------------------------------|
| 1. Electrical connection | 6. Liquid soap connection | 11. Door opening (Ø 460mm) |
| 2. Hot water | 7. Drain | 12. Fuses |
| 3. Cold water hard | 8. Soap dispenser | 13. USB port |
| 4. Cold water soft | 9. Control panel | 14. Electrical connection to liquid soap pumps |
| 5. Main switch | 10. Button CENTRALSTOP | |